

PSW NEW Make & Brake Unit

The EnerQuip FR machine has been designed with the ever-changing industry requirements. Low torque ability as standard circa. 100 ft lb. Automated self-leveling tool support jacks hydraulically fully floating heads - no need for additional utilities i.e. compressed air Multiple graph overlay and make-up trend - instantly highlights any anomalies in make up.

| | |
|--|--|
| Headstock Clamp Range: 2 3/8"-22" | Make Torque - Min (ft lbs): 100 ft lbs |
| Tailstock Clamp Range: 2 3/8"-22" | Make Torque - Max (ft lbs): 100,000 ft lbs |
| Clamping Jaws 6 off per Head | Break Torque - Max (ft lbs): 100,000 ft lbs |
| Bed Length 15Ft | Control System, EnerQuip Torque Turn Software |

HEADSTOCK

Fully floating head and tailstock allows for any pipe deflection without damaging threads. Fully extendable clamping jaws that grip the machine's entire pipe range without the requirement to change jaws.



TAILSTOCK

Top open Tailstock option allows safe, efficient loading/unloading of tubulars



MACHINE SKID

Fully programmable support jacks to ensure pipe alignment

HYDRAULIC POWER UNIT c/w Control Panel

Standalone hydraulic power pack 30KW, 415V, 50/60HZ Control panel



TCS Software

The heart of our unit is our industry leading software. This allowed us to work closely with the principal thread licensees to ensure that our software exceeds the current requirements and is flexible enough to evolve as requirements change.

